

LAQUA

LAQUA WQ-300 Series Smart Handheld Water Quality Meters



pH | ORP | Dissolved Oxygen | Conductivity | Resistivity | Total Dissolved Solids | Salinity | Ion



www.horiba-laqua.com



LAQUA WQ-300 Series

Smart Handheld Water Quality Meters



Meter and electrode shown in actual size



Scan code to view LAQUA WQ-300 Series feature video online



Visit the **HORIBA LAQUA Singapore** Channel on YouTube and subscribe to see more of our videos.





Large Colour Graphic LCD Screen with Backlight

All models have colour graphic digital LCD screen (70 x 52 mm) with white LED backlight for easy viewing.



Built-in Foldable Meter Stand

Collapsible meter stand is built-in at the back of the meter for convenient usage and storage.



IP67 Waterproof and Dustproof

Fully protected from dust and capable of withstanding water immersion up to 1 meter depth for 30 mins.



Battery and USB Powered

Four AA batteries or battery pack with micro USB cable can be used to power the meter in the field. USB charger plugged to a power outlet can be used for an uninterrupted operation in the lab.



Eco-friendly, Shock-proof, Scratch Resistant, and Non-slip

Apart from their high impact strength, the polycarbonate and TPE materials are also long-lasting and recyclable. The TPE provides non-slip grip and is not easily damaged by abrasion.




Built-in Sensor Holders

Three grooves on the meter housing serve as sensor holders.

LAQUA WQ-300 Series

Smart Handheld Water Quality Meters



Efficient Sensor Locking Mechanism

The push-pull connectors deliver a simple yet fast and strong method to connect and disconnect sensors. The lock is released only when the outer sleeve of the connector is pulled back so accidental disconnection is prevented.

No Sensor Adapter Needed

Each sensor head has two grooves and one hook which can be used to attach up to three sensor heads.



Sensor's LED Light as Reading Stability Indicator

Blue LED light on the sensor head flashes until the reading is stable.



Compatible with Conventional Electrodes having BNC and Phono Connectors and Long Cables

With 300-BNC sensor head adapter, conventional electrodes with BNC and phono connectors can be connected to the meter. Also, electrodes with up to 10m cable can be used without noise problem.



Hands-free Testing

Hang the meter using a wrist strap or lanyard, place it into the carrying case, or mount it to a wall while in use.

Ergonomic Design

The black meter housing is made of polycarbonate material covered with a layer of thermoplastic elastomer (TPE) material. It is lightweight, comfortable to touch, and suitable for field applications.



Rugged Carrying Case

Keeps all your equipment organized and secure.

Storage Space

Compartment for instruction manual and accessories.

DO Sensor Guard



Bottle Stand

Secures the bottles upright while doing calibration.



Bottle Holders

Stores up to 8 x 60ml bottles of Standard Solutions

Cable Space

For sensors with extra long cables

Cable Winder

Organize sensor cables neatly.

Sensor Holders

Holds pH, Conductivity, and DO sensors

English
日本語
Français
Deutsch
Español
Português
中文



Multi-Language Options

Available in several languages—English, Japanese, French, German, Spanish, Portuguese, and Chinese.




Simultaneous Calibrations and Measurements

Applicable for dual- and triple-channel models.

LAQUA WQ-300 Series | Smart Handheld Water Quality Meters

Versatile Channels & Adaptive Display


Single-, dual-, and triple-channel models are available. Sensors can be connected to any channel in dual- and triple-channel models and the meter screen automatically adjusts.



Automatic Sensor Recognition

Sensor info, calibration data, and measurement setup stored in sensor head are viewable in the meter when sensor is connected.

26 Jan 2019 10:30	
SAMPLE - 1	
Ch 1	25.0°C (ATC)
pH	
7.000	
pH	0.0 mV
Measurement	



26 Jan 2019 10:30	
pH Setup	
pH Resolution	0.01 ▶
Buffer Group	USA ▶
CAL Alarm	OFF ▶
Temp. Type	ATC ▶
CAL Data Clear	▶
Set	

26 Jan 2019 10:30	
Ch1 Calibration Data	
Ch 1 Latest CAL Date	:29 Aug 2019
Sensor Status	: Excellent
Ave. Slope	: 97.8%
Offset	: -1.9mV
USA	
4.01 7.00 10.01	
P	Date Time Cal Value mV °C %
1	29 Aug 2019 14:55 4.00 168.8 23.4 96.9
2	29 Aug 2019 14:53 7.00 -2.1 23.6 98.7
3	29 Aug 2019 14:56 10.03 -177.6 23.3
4	
5	
Measurement	

26 Jan 2019 10:30	
Ch1 Sensor Info.	
Sensor	
Model	: 300pH - 2
SN	: ABCD1234
SW Ver.:	0.3.6
Cartridge	
Model	: 300-P-C
SN	: 123456
Set	



Data Transfer via USB or Wireless Communication


Meter stores up to 10,000 data with date/time stamp. Transfer data from meter to computer seamlessly via USB cable or wirelessly via Wi-Fi. Each meter comes with a wireless SD card.

Scan code to view LAQUA WQ-300 Series USB Data Transfer video

Scan code to view LAQUA WQ-300 Series Wireless Data Transfer video


Printer Communication

Print data using a printer via 25-pin D-sub printer cable.




Sensor Status Indicator


Sensor icon presents the sensor condition after calibration.



Temperature Sensor Indicator




Temperature sensor is connected to meter




Temperature sensor is not connected to meter

Sample ID




Use up to eight characters for creating Sample ID.

Calibration Data




Right arrow button shows the latest calibration data.


Measurement Modes



Auto Stable



Auto Hold



Real Time

LAQUA WQ-300 Series | Smart Handheld Water Quality Meters

Customizable Meter Kit

Create a custom meter kit by selecting the meter, sensor, and accessories.

DO COND nH
Multi-parameter combinations



nH nH nH
Single parameter combinations



Up to 55 possible meter + sensor combinations

5 Combinations

WQ-310
Single Channel



15 Combinations

WQ-320
Dual Channel



35 Combinations

WQ-330
Triple Channel



Choose your meter*:

Choose your sensor kit:

Meter only

Sensor (2.0m cable) kit

Sensor (5.0m cable) kit

WQ-310-K
Single Channel
3200832605



WQ-320-K
Dual Channel
3200832606



WQ-330-K
Triple Channel
3200832607



WQ 300 PH Kit 2M

pH pH Sensor Kit with USA pH Buffers - 3200820791



WQ 300 PH Kit 5M

pH pH Sensor Kit with USA pH Buffers - 3200820791



WQ 300 EC Kit 2M

COND Conductivity Sensor Kit with Conductivity Standards - 3200820792



WQ 300 EC Kit 5M

COND Conductivity Sensor Kit with Conductivity Standards - 3200820792



WQ 300 DO Kit 2M

DO DO Sensor - 3200780940



WQ 300 DO Kit 5M

DO DO Sensor - 3200780942



WQ 300 ION Kit 2M

Ion Ion Sensor Kit



WQ 300 ORP Kit 2M

ORP ORP Sensor Kit



*Includes carrying case, 4 x AA batteries, wireless SD card, user manual, and quick guide




Sensor head with built-in digital circuit

Retains sensor and measurement information

Sensor cartridge

Replaceable, cost efficient and environment-friendly



Smart Digital Sensor

HORIBA's Smart digital sensor technology

■ Maintenance-free, gel-filled pH sensor

No electrolyte refilling required

- KCl gel electrolyte
- Double junction reference
- Porous sintered polyethylene junction
- Built-in temperature sensor
- Rugged polycarbonate body
- Replaceable pH sensor cartridge
- pH sensor heads with 2m and 5m cables are available



■ 4-Cell conductivity sensor

Wide range of conductivity measurements possible


- From clean water to industrial wastewater, the 4-cell type can measure a variety of samples with different conductivity
- Built-in temperature sensor
- Durable epoxy / carbon body
- Replaceable conductivity sensor cartridge
- Conductivity sensor heads with 2m and 5m cables are available



■ Optical dissolved oxygen (DO) sensor

Longer usable life with excellent performance

- Easy to handle – not affected with sample flow velocity, not sensitive to hydrogen sulfide, DO sensor cap replacement after 1-2 years*
- Built-in temperature sensor
- Comes with replaceable DO sensor cap, air calibration bottle and Stainless Steel DO Sensor Protective Guard
- DO sensor heads with 2m and 5m cables are available



■ Ion sensor head

Compatible with conventional ion selective electrodes

- Accepts all combination ion selective electrodes with BNC connector
- Requires sensor head adapter
- Comes with 2m cable



■ ORP sensor head

Compatible with conventional ORP electrodes

- Accepts 9300-10D and other combination ORP electrodes with BNC connector
- Requires sensor head adapter
- Comes with 2m cable



*Depending on application, handling, and maintenance

LAQUA WQ-300 Series | Smart Handheld Water Quality Meters

Sensor and Meter Specifications

pH Sensor Head pH / mV / Temp (°C/°F)		
Model	300PH-2	300PH-5
Part No.	3200812206	3200812207
pH Range	-2.00 to 20.00 pH -2.000 to 20.000 pH	
Resolution	-2.00 to 20.00: 0.01 pH -2.000 to 20.000: 0.001 pH	
Accuracy	-2.00 to 20.00: ±0.01 -2.000 to 20.000: ±0.005	
Calibration Points	Up to 6	
pH Buffer Groups	USA, DIN, NIST, NIST10, Custom	
mV Range	±1000.0 mV	
Resolution	0.1 mV	
Accuracy	±0.1 mV	
Temperature Range	-30.0 to 130.0 °C -22.0 to 266.0 °F	
Resolution	0.1 °C / °F	
Accuracy	±0.5 °C / ±0.9 °F	
Calibration Option	Yes	
Body Material	ABS / Polycarbonate	
Length and Diameter	85 x 30 mm	
Connector	Push-pull	
Cable Length	2 m	5 m

pH Sensor Cartridge pH/mV/Temp (°C/°F)	
Model	300-P-C
Part No.	3200786363
pH Range	-2.00 to 20.00 pH -2.000 to 20.000 pH
Temperature Range	0 to 80 °C -32.0 to 176.0 °F
Junction Material	Porous sintered polyethylene
Double Junction	Yes
Temperature Sensor	Built-in
Length and Diameter	110 x 16 mm
Body Material	Polycarbonate, glass bulb

Dissolved Oxygen Sensor DO (mg/L, %) / O ₂ / Temp (°C/°F)		
Model	300-D-2	300-D-5
Part No.	3200780940	3200780942
Dissolved Oxygen (DO) Range	0.00 to 20.00 mg/L 0.0 to 200.0 %	
Resolution	0.01 mg/L, 0.1%	
Accuracy	±0.2 mg/L, ±2 %	
Salinity Compensation	Auto: by conductivity sensor / Manual: 0.0 to 40.0 ppt	
Barometric Pressure Compensation	Auto: by built-in barometer / Manual: 10.0 to 199.9 kPa	
Calibration Points	Up to 2	
Oxygen Range	0.0 to 50.0%	
Resolution	0.1%	
Accuracy	±0.5%	
Temperature Range	-30.0 to 130.0 °C -22.0 to 266.0 °F	
Resolution	0.1 °C / °F	
Accuracy	±0.5 °C / ±0.9 °F	
Calibration Option	Yes	
Body Material	ABS / Polycarbonate	
Length and Diameter	200 x 16 mm	
Connector	Push-pull	
Cable Length	2 m	5 m
Sensor cap included	1	


Dissolved Oxygen Sensor Cap	
Model	300-D-M
Part No.	3200781554
DO Range	0.00 to 20.00 mg/L 0.0 to 200.0 %
Temperature Range	0 to 50.0 °C 32.0 to 122.0 °F
Length and Diameter	10 x 16 mm
Body Material	PVC, PMMA

Conductivity Sensor Head EC / Sal / TDS / Res / Temp (°C/°F)		
Model	300-C-2	300-C-5
Part No.	3200784468	3200812202
Conductivity Range	μS/cm	μS/m
	0.000 to 0.199	0.0 to 19.9
	0.200 to 1.999	20.0 to 199.9
	2.00 to 19.99	200 to 1999
	20.0 to 199.9	mS/m
	200 to 1999	20.0 to 199.9
	mS/cm	200 to 199.9
Resolution	2.00 to 19.99	200 to 1999
	20.0 to 199.9	S/m
Accuracy	2.00 to 2000	
Reference Temperature	Auto ranging, up to 4 significant digits	
Temperature Coefficient	± 0.5% full scale of each range > 200 mS/cm (20.0 S/m): ± 1.5% full scale	
Calibration Points	15 to 30 °C	
Units	0.00 to 10.00 %/°C	
Salinity Range	Up to 4 (Auto) / Up to 5 (Manual)	
Resolution	S/cm, S/m	
Accuracy	0.00 to 80.00 ppt 0.000 to 8.000 %	
Salinity Curves	0.01 ppt, 0.001 %	
Calibration Option	± 0.5% of reading or ± 0.01 ppt, whichever is greater	
Total Dissolved Solids (TDS) Range	NaCl, Seawater (UNESCO 1978)	
Resolution	Yes	
Accuracy	0.01 mg/L to 200,000 mg/L	
TDS Curves	0.01 minimum, 4 significant digits	
Resistivity Range	± 0.5% of reading or ± 0.1 mg/L, whichever is greater	
	Ω•cm	Ω•m
	0.1 to 199.9	0.001 to 1.999
	200 to 1999	2.00 to 19.99
	kΩ•cm	20.0 to 199.9
	2.00 to 19.99	200 to 1999
	20.0 to 199.9	kΩ•m
	200 to 1999	2.00 to 19.99
	MΩ•cm	20.0 to 199.9
	2.00 to 19.99	200 to 2000
20.0 to 200.0		
Resolution	Auto ranging, up to 4 significant digits	
Accuracy	± 0.5% full scale of each range > 200 mS/cm (20.0 S/m): ± 1.5% full scale	
Temperature Range	-30.0 to 130.0 °C -22.0 to 266.0 °F	
Resolution	0.1 °C / °F	
Accuracy	±0.5 °C / ±0.9 °F	
Calibration Option	Yes	
Body Material	ABS / Polycarbonate	
Length and Diameter	85 x 30 mm	
Connector	Push-pull	
Cable Length	2 m	5 m

4-Cell Conductivity Sensor Cartridge	
Model	300-4C-C
Part No.	3200780928
Cell Constant	0.172 cm ⁻¹
Conductivity Range	10 μS/cm to 2000 mS/cm
Temperature Range	0 to 100 °C 32.0 to 212.0 °F
Temperature Sensor	Built-in
Length and Diameter	110 x 16 mm
Body Material	Epoxy, carbon

Ion Sensor Head Ion / mV / Temp (°C/°F)	
Model	300-I-2
Part No.	3200812203
Ion Range	(mg/L, mmol/L) 0.000 to 0.999, 1.00 to 9.99, 10.0 to 99.9, 100 to 999, 1000 to 9990, 10000 to 99900
Resolution	0.001 minimum, 3 significant digits
Accuracy	±0.1 mV
Calibration Points	Up to 5
mV Range	±1000.0 mV
Resolution	0.1 mV
Accuracy	±0.1 mV
Temperature Range	-30.0 to 130.0 °C -22.0 to 266.0 °F
Resolution	0.1 °C / °F
Accuracy	±0.5 °C / ±0.9 °F
Calibration Option	Yes
Body Material	ABS / Polycarbonate
Length and Diameter	85 x 30 mm
Connector	Push-pull
Cable Length	2 m

ORP Sensor Head ORP / Temp (°C/°F)	
Model	300-O-2
Part No.	3200812204
ORP Range	-2000 to +2000 mV
Resolution	< ±1000.0 mV: 0.1mV ≥ 1000.0 mV: 1 mV
Accuracy	< ±1000.0 mV: ±0.1 mV ≥ 1000.0 mV: ±1 mV
Calibration Option	Yes
Temperature Range	-30.0 to 130.0 °C -22.0 to 266.0 °F
Resolution	0.1 °C / °F
Accuracy	±0.5 °C / ±0.9 °F
Calibration Option	Yes
Body Material	ABS / Polycarbonate
Length and Diameter	85 x 30 mm
Connector	Push-pull
Cable Length	2 m



Model	WQ-310-K	WQ-320-K	WQ-330-K
Part No.	3200832605	3200832606	3200832607
Channel	Single	Dual	Triple
Memory	10,000 Data with date and time stamp		
Data Log	Auto / Manual		
Measurement Modes	Auto Stable / Auto Hold / Real Time		
Calibration Alarm	Programmable: 0 to 400 days		
Auto Power Off	Programmable: 0 to 60 minutes		
Real-time Clock	Available		
Sensor Status	On display		
Diagnostics	Error codes		
Language	English, Japanese, French, German, Spanish, Portuguese, Chinese		
PC Communication	Via micro USB cable or wireless		
Printer Communication	Via 25-pin D-sub printer (RS232) cable		
Meter Input	Push-pull connector		
Display	Color graphic TFT-LCD, 3.5 inches		
Housing	IP67, shock & scratch resistant, non-slip (ABS / polycarbonate)		
Power Requirement	4 x AA batteries / battery pack or USB charger with micro USB cable		
Battery Life	> 100 hours (with display brightness 3 and no sensor connected)		
Dimensions	220 (L) x 90 (W) x 34 (H) mm		
Weight	Approx. 400g (batteries included), 320 g (batteries excluded)		
Standard Accessories	Carrying case, 4 x AA batteries, wireless SD card, manual, and quick guide		

LAQUA WQ-300 Series | Smart Handheld Water Quality Meters

Accessories & Solutions

Product	Part Number	Description
pH Buffer Solutions		
250-PH-4	1300045600	pH 4,01 buffer solution, 250 ml in dosing bottle, NIST Traceable with certificate, accuracy $\pm 0,01$ @ 25°C
500-PH-4	1300045602	pH 4,01 buffer solution, 500 ml in dosing bottle, NIST Traceable with certificate, accuracy $\pm 0,01$ @ 25°C
1000-PH-4	1300045599	pH 4,01 buffer solution, 1 ltr in dosing bottle, NIST Traceable with certificate, accuracy $\pm 0,01$ @ 25°C
250-PH-7	1300045607	pH 7,00 buffer solution, 250 ml in dosing bottle, NIST Traceable with certificate, accuracy $\pm 0,01$ @ 25°C
500-PH-7	1300045608	pH 7,00 buffer solution, 500 ml in dosing bottle, NIST Traceable with certificate, accuracy $\pm 0,01$ @ 25°C
1000-PH-7	1300045606	pH 7,00 buffer solution, 1 ltr in dosing bottle, NIST Traceable with certificate, accuracy $\pm 0,01$ @ 25°C
250-PH-10	1300045604	pH 10,01 buffer solution, 250 ml in dosing bottle, NIST Traceable with certificate, accuracy $\pm 0,02$ @ 25°C
500-PH-10	1300045605	pH 10,01 buffer solution, 500 ml in dosing bottle, NIST Traceable with certificate, accuracy $\pm 0,02$ @ 25°C
1000-PH-10	1300045603	pH 10,01 buffer solution, 1 ltr in dosing bottle, NIST Traceable with certificate, accuracy $\pm 0,02$ @ 25°C
ORP Standard Solutions		
250-ORP-200	1300045637	200 mV Redox/ORP solution, 250 ml round brown bottle, accuracy ± 5 mV / 25°C
250-ORP-475	1300045636	475 mV Redox/ORP solution, accuracy ± 5 mV / 25°C, 250 ml dosing bottle
500-ORP-475	1300045635	475 mV Redox/ORP solution, 500 ml dosing bottle, accuracy ± 5 mV @ 25°C
500-ORP-650	1300045634	650 mV Redox/ORP solution, 500 ml dosing bottle, accuracy ± 5 mV @ 25°C
Internal Filling Solutions		
300	3200043640	Internal Solution for Reference Electrode Type 300, pH, 250ml
310	3200043622	Internal Filling Solution for H-7 and old type electrodes
350	3200043623	Powder for preparing Reference Electrode Internal Solution, 500g. Dissolve in 2L of pure water
Conductivity Standard Solutions		
250-EC-84	1300045609	84 uS/cm Calibration Solution, 250 ml dosing bottle with certificate, accuracy $\pm 1\%$, KCl
500-EC-84	1300045632	84 uS/cm Calibration Solution, 500 ml dosing bottle with certificate, accuracy $\pm 1\%$, KCl
1000-EC-84	1300045633	84 uS/cm Calibration Solution, 1 ltr dosing bottle with certificate, accuracy $\pm 1\%$, KCl
250-EC-147	1300051602	147 uS/cm Calibration Solution, 250 ml dosing bottle with certificate, accuracy $\pm 1\%$, KCl
250-EC-1413	1300045595	1,413 uS/cm Calibration Solution, 250 ml dosing bottle with certificate, accuracy $\pm 1\%$, (25°C)=0.01M KCl
500-EC-1413	1300045638	1,413 uS/cm Calibration Solution, 500 ml dosing bottle with certificate, accuracy $\pm 1\%$, (25°C)=0.01M KCl
1000-EC-1413	1300045591	1,413 uS/cm Calibration Solution, 1 ltr dosing bottle with certificate, accuracy $\pm 1\%$, (25°C)=0.01M KCl
250-EC-1288	1300045590	12,88 mS/cm Calibration Solution, 250 ml dosing bottle with certificate, accuracy $\pm 1\%$, (25°C)=0.1M KCl
500-EC-1288	1300045639	12,88 mS/cm Calibration Solution, 500 ml dosing bottle with certificate, accuracy $\pm 1\%$, (25°C)=0.1M KCl
1000-EC-1288	1300045588	12,88 mS/cm Calibration Solution, 1 ltr dosing bottle with certificate, accuracy $\pm 1\%$, (25°C)=0.1M KCl
250-EC-1118	1300045630	111,8 mS/cm Calibration Solution, 250 ml dosing bottle with certificate, accuracy $\pm 1\%$ (25°C)= 1M KCl
500-EC-1118	1300045660	111,8 mS/cm Calibration Solution, 500 ml dosing bottle with certificate, accuracy $\pm 1\%$ (25°C)= 1M KCl
1000-EC-1118	1300045631	111,8 mS/cm Calibration Solution, 1 ltr dosing bottle with certificate, accuracy $\pm 1\%$ (25°C)= 1M KCl
Ion Standard Solutions		
500-NH4-SH	3200697171	1000 mg/L Ammonium Ion Standard Solution, 500ml
500-NH4-SL	3200697172	100 mg/L Ammonium Ion Standard Solution, 500ml
500-CA-SH	3200697175	1000 mg/L Calcium Ion Standard Solution, 500ml
500-CA-SL	3200697176	100 mg/L Calcium Ion Standard Solution, 500ml
500-CL-SH	3200697167	1000 mg/L Chloride Ion Standard Solution, 500ml
500-CL-SL	3200697168	100 mg/L Chloride Ion Standard Solution, 500ml
500-F-SH	3200697163	1000 mg/L Fluoride Ion Standard Solution, 500ml
500-F-SL	3200697164	100 mg/L Fluoride Ion Standard Solution, 500ml
500-NO3-SH	3200697179	1000 mg/L Nitrate Ion Standard Solution, 500ml
500-NO3-SL	3200697180	100 mg/L Nitrate Ion Standard Solution, 500ml
500-K-SH	3200697183	1000 mg/L Potassium Ion Standard Solution, 500ml
500-K-SL	3200697184	100 mg/L Potassium Ion Standard Solution, 500ml
Ionic Strength Adjustors		
500-NH3-ISA	3200697174	Ammonia Ionic Strength Adjuster, 500ml
500-CA-ISA	3200697178	Calcium Ionic Strength Adjuster, 500ml
500-CL-ISA	3200697170	Chloride Ionic Strength Adjuster, 500ml
500-F-TISAB	3200697166	Fluoride Ionic Strength Adjuster, 500ml
500-NO3-ISA	3200697182	Nitrate Ionic Strength Adjuster, 500ml
500-K-ISA	3200697186	Potassium Ionic Strength Adjuster, 500ml



NIST traceable pH Buffer Solutions



Calcium Ion Electrode Solutions



Chloride Ion Electrode Solutions



Fluoride Ion Electrode Solutions



Potassium Ion Electrode Solutions




Ammonia Ion Electrode Solutions



Nitrate Ion Electrode Solutions

Cleaning Solutions

Part No.	Model	Description
3014028653	220	Cleaning solution for removing inorganic sample residues, 50ml x 2pcs 
3200530494	230	Cleaning solution for removing inorganic and organic sample residues, Solution A (30ml) & Solution B (100ml)
3200366771	250	Cleaning solution for removing proteins, 400ml



220

250

Cartridges, Ion Selective Electrodes, and Tips

Part No.	Model	Description
3200786363	300-P-C	pH sensor cartridge
3200780928	300-4C-C	4-cell conductivity sensor cartridge
3200781554	300-D-M	Optical DO sensor cap
3014046710	9300-10D	ORP electrode with flat platinum tip and temperature sensor
3200698386	5002S-10C	Ammonia electrode (combination)
3200697410	6583S-10C	Calcium ion selective electrode (combination)
3200697407	6560S-10C	Chloride ion selective electrode (combination)
3200693774	6561S-10C	Fluoride ion electrode (combination)
3200697408	6581S-10C	Nitrate ion selective electrode (combination)
3200697409	6582S-10C	Potassium ion selective electrode (combination)
3200705774	-	Ammonia electrode membrane caps (3 pcs.)
3200697414	7683S	Calcium electrode tip
3200697411	7660S	Chloride electrode tip
3200693606	7661S	Fluoride electrode tip
3200697412	7681S	Nitrate electrode tip
3200697413	7682S	Potassium electrode tip



230

Cleaning Solutions



Ammonia electrode membrane caps



Calcium electrode tip



Chloride electrode tip



Fluoride electrode tip



Nitrate electrode tip



Potassium electrode tip



300-BNC Sensor Head Adapter

Accessories

Part No.	Model	Description
3200821465	300-BNC	Sensor head adapter
3014028368	X-51	Digital simulator (300-BNC is required for pH, ORP, and Ion sensor heads)
3014030146	—	Printer for GLP / GMP compliance, 120V US version (printer cable is sold separately)
3014030147	—	Printer for GLP / GMP compliance, 230V EU version (printer cable is sold separately)
3200779638	—	25-pin D-sub printer (RS232) cable, 1.5m
3014030149	—	Printer paper, 20 rolls
3014030150	—	Printer ink ribbon, 5pcs/pack
3200828646	—	Black pH sensor tip guard (for 200 series, 300 series), 3pcs/pack
3200043508	—	Electrode protection caps, 5pcs/pack

*Sensors carry 6-month warranty against manufacturing defects.



Black pH sensor tip guard



Electrode protection cap



Printer ink ribbon



Printer paper



25-pin D-sub printer cable



Printer



X-51 Digital Simulator

With over 60 years of engineering excellence, HORIBA's diverse range of water quality analyzers and electrodes are ideal for everyday laboratory needs through to the most demanding of applications. Visit our website for a wealth of useful information and water quality measurement tips to help you obtain the best results in your work.



Benchtop Meters

Developed using extensive feedback from users, our new LAQUA meters deliver the best solution for water quality analysis. Our LAQUA website features an online 'Selection Guide' to enable you to find the perfect LAQUA meter and electrode for your need.



Handheld Meters

In the lab, in the field or anywhere you need it. LAQUA Handheld meters are designed for use with one hand and with an IP67 waterproof rating and shock-resistant casing. Meters can be used for long periods, even in dark places, making it ideal for field measurements in rivers and lakes.



Pocket Meters

Analyzing water quality is simplified when using our LAQUAAtwin range of meters. Designed to produce accurate and reliable results. Anyone, anywhere, at any time can measure samples easily with a LAQUAAtwin meter. See just how good they are at our website.



Electrodes

Various electrodes to match any application. A wide range of products for both benchtop and portable systems are available, including easy and reliable standard models, application-focused models for small samples or large containers, and special electrodes for specific sample characteristics.



Application Notes

LAQUAAtwin pocket meters offer quick and convenient alternative to analyze important parameters with high accuracy. Several application notes are available at (<http://goo.gl/znwE6j>) detailing the use of LAQUAAtwin and the results achieved for the respective applications. Additional application notes will be added when available.



RoHS



- The contents of this catalog are subject to change without prior notice, and without any subsequent liability to this company.
- The color of the actual products may differ from the color pictured in this catalog due to printing limitations.
- It is strictly forbidden to copy the content of this catalog in part or in full.
- All brand names, product names and service names in this catalog are trademarks or registered trademarks of their respective companies.
- Windows is a registered trademark of Microsoft Corporation in the United States and other countries.

Europe, Middle East, & Africa

HORIBA UK Limited
 Kyoto Close, Moulton Park,
 Northampton NN3 6FL
 Phone: +44 1604 642500
 e-mail: waterquality@horiba.com